

Temperature switch series T4 and T7

General purpose or Ex-proof according UL or ATEX (EEx d or EEx ia)

Accuracy: $\pm 1\%$

Features

- Ambient temperature up to 60 °C for EEx applications
- Ex II 2 GD or Ex II 1 GD
- Class 1 Division 1 Gr. B, C and D according UL
- Protection IP54, IP66 or NEMA 4, 4X, 7, 9 and 13 (UL)
- Rigid stem and capillary types up to 15 m

Ranges

-40/16 °C up to 260/400 °C

-40/60 °F up to 500/750 °F

Applications

Chemical and petrochemical industry

Machine and apparatus construction

Food and beverage industry

Pulp and paper industry



Technical specification	T4 series	T7 series	
Construction	Weatherproof	Ex-proof according UL CSA on request	Ex-proof according CENELEC (ATEX) EN 50 0-14, -18, -20
Switch functions	One setpoint, single pole double throw (SPDT) or 2 times SPDT (2SPDT)		
Adjustable range	From 15 % to 100 %, below 15 % consult factory		
Deadband	From 0,5 % to 15 % F.S., depending on range and microswitch		
Measuring principle	Piston/cylinder system actuated by a vapor pressure thermal system, SAMA Class II system		
Range [°C]	-40/16	-20/40	20/95 65/125 110/190 175/275 260/400
[°F]	-40/60	0/100	75/205 150/260 235/375 350/525 500/750
Limits (temperature ranges)	-40/16 °C, -20/40 °C, 20/95 °C and 65/125 °C		110/190 °C 175/275 °C 260/400 °C
max. temperature	204 °C		260 °C 371 °C 482 °C
Stem diameter	3/8" (9,5 mm)		
Stem length	2 3/4" (70 mm)	4" (102 mm)	6" (152 mm) 9" (229 mm) 12" (305 mm)
Bulb length (capillary type)	3" (76 mm)		
Capillary length	5' (1,5 m)	10' (3,0 m)	15' (4,5 m) 20' (6,0 m) 25' (7,5 m) longer lengths on request
Process connection	1/2 NPT male for rigid stem, 1/2 NPT bushing sliding on capillary or bulb		
Connection location	Lower		
Material			
Connection	Stainless steel 316 (1.4401)		
Bushing	Stainless steel 316 (1.4401)		
Capillary and armor	Stainless steel 316 (1.4401)		
Housing	Aluminum, epoxy coated black		
Accuracy	1,0 % F.S.		
Electrical specification			
Microswitch ratings	From 6 A 30 VDC up to 22 A 250 VAC (see microswitch table)		
Ex-proof		Class 1 Div. 1 Gr. B, C and D Class 2 Div. 1 Gr. E, F and G	EEx d IIC T6 Sira 02 ATEX 1391
Intrinsically safe			EEx ia IIC T4 Sira 04 ATEX 2081
Electrical connection	3/4 NPT female, optional cable glands, 1/2 NPT with reducer bushing, M20x1,5, others on request		
General specification			
Permissible			
Ambient temperature	-25 ... 65 °C		-20 ... 60 °C
Storage temperature	-40 ... 60 °C		
Effect	max. 0,4 % / 10 K ref. 20 °C		
Protection according UL	NEMA 4, 4X and 13		NEMA 7 and 9
Protection according EN 60 529/IEC 529	IP54, optional IP66		IP66
CE-mark	Low voltage regulations EN 61 010-1, EN 60 947-1		
Mounting	Direct, wall mounted or rigid stem, 2" pipe mounting (TM) with capillary system		
Weight rigid stem/capillary [kg]	1,2/1,7 (with 1 m capillary)		1,7/2,0 (with 1 m capillary)
Accessories, options	Thermowells screwed or flanged		

